

445/45R19.5 164J NOKIAN TYRES HAKKA TRUCK TRAILER 2

Improved mileage and stability for long distance and regional transport

PRODUCT CODE	T675359
APPLICATION	Trailer
LI / SPEED SYMBOL	164J
RIM RECOMMENDED	14.00
RIM PERMITTED	15.00
TYPE APPROVAL	E4 0058483, E4 0416947 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	100	7710	7940	8180	8410	8640	8870	9100	9330	9550	9780	10000

TIRE DIMENSIONS

OVERALL DIAMETER	898 mm
TIRE WIDTH	438 mm
STATIC LOADED RADIUS	407 mm
ROLLING CIRCUMFERENCE	2712 mm
PATTERN DEPTH	13 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/