

445/45R19.5 164J NOKIAN TYRES HAKKA TRUCK TRAILER 2

Improved mileage and stability for long distance and regional transport

PRODUCT CODE	T675359
APPLICATION	Trailer
LI / SPEED SYMBOL	164J
RIM RECOMMENDED	14.00
RIM PERMITTED	15.00
TYPE APPROVAL	E4 0058483, E4 0416947 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	62.5	17000	17505	18035	18540	19050	19555	20060	20570	21055	21560	22045

TIRE DIMENSIONS

OVERALL DIAMETER	35.4 in
TIRE WIDTH	17.2 in
STATIC LOADED RADIUS	16 in
ROLLING CIRCUMFERENCE	106.8 in
PATTERN DEPTH	16/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/