

385/55R22.5 160K NOKIAN TYRES HAKKA TRUCK TRAILER

Confidence on any road, in any weather – trailer tire for the most demanding transports

PRODUCT CODE	T675304
APPLICATION	Trailer
LI / SPEED SYMBOL	160K
RIM RECOMMENDED	11.75
RIM PERMITTED	12.25
TYPE APPROVAL	E4 0058473, E4 0416946 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	67.5	15300	15765	16225	16690	17150	17615	18055	18495	18960	19400	19840

TIRE DIMENSIONS

OVERALL DIAMETER	39.1 in
TIRE WIDTH	14.9 in
STATIC LOADED RADIUS	18 in
ROLLING CIRCUMFERENCE	118.8 in
PATTERN DEPTH	19/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/