

265/70R19.5 143/141J NOKIAN TYRES HAKKA TRUCK TRAILER

Confidence on any road, in any weather – trailer tire for the most demanding transports

PRODUCT CODE	T675268
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0046923, E4 0212339 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	100	4400	4530	4670	4800	4930	5060	5190	5320	5450
Dual	100	8310	8570	8820	9070	9320	9570	9810	10060	10300

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	871 mm
TIRE WIDTH	252 mm
STATIC LOADED RADIUS	403 mm
ROLLING CIRCUMFERENCE	2648 mm
MIN. DUAL SPACING	295 mm
PATTERN DEPTH	14 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	C
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/