

# 295/80R22.5 154/149J NOKIAN TYRES HAKKAPELIITTA CITY BUS

Durability and winter grip for city buses

PRODUCT CODE	T675356
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	154/149J
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0058480, E4 0416951 S2W2R3B



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	100	6050	6240	6420	6600	6790	6970	7140	7320	7500
Dual	100	10490	10810	11130	11450	11760	12070	12380	12690	13000

## TIRE DIMENSIONS

STATIC LOADED RADIUS	489 mm
ROLLING CIRCUMFERENCE	3184 mm
MIN. DUAL SPACING	335 mm
PATTERN DEPTH	18.5 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)