

275/70R22.5 150/148J NOKIAN TYRES HAKKAPELIITTA CITY BUS

Durability and winter grip for city buses

PRODUCT CODE	T675218
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	150/148J (152/148E)
RIM RECOMMENDED	8.25
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0037368, E4 029083 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	62.5	11375	11730	12080	12435	12765	13095	13450	13780	14110	14440	14770
Dual	62.5	21405	22070	22730	23370	24010	24650	25285	25905	26545	27160	27780

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Dual	42.5	21405	22070	22730	23370	24010	24650	25285	25905	26545	27160	27780
Single	42.5	12060	12435	12810	13160	13535	13890	14240	14595	14945	15300	15655

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	38.1 in
TIRE WIDTH	10.8 in
STATIC LOADED RADIUS	17.9 in
ROLLING CIRCUMFERENCE	115.9 in
MIN. DUAL SPACING	12.2 in
PATTERN DEPTH	26/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	72 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/