

275/70R22.5 148/145M NOKIAN TYRES HAKKAPELIITTA TRUCK D

Superior grip and stability in the long haul

PRODUCT CODE	T675233
APPLICATION	Drive
LI / SPEED SYMBOL	148/145M
RIM RECOMMENDED	8.25
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0040278, E4 0210185 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	80	10715	11025	11355	11685	11995	12325	12630	12965	13270	13580	13890
Dual	80	19710	20325	20920	21515	22110	22685	23280	23855	24425	25000	25575

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	37.7 in
TIRE WIDTH	10.9 in
STATIC LOADED RADIUS	17.5 in
ROLLING CIRCUMFERENCE	114.6 in
MIN. DUAL SPACING	12.2 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	75 dB
NOISE WAVES	B
STUDDABLE	Marked stud positions on tread Number of studs 146 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/