

295/80R22.5 152/148M NOKIAN TYRES HAKKAPELIITTA TRUCK D2

PRODUCT CODE	T675320
APPLICATION	Drive
LI / SPEED SYMBOL	152/148M (154/150L)
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0058479, E4 0416948 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	130	5730	5900	6080	6250	6420	6590	6760	6930	7100
Dual	130	10170	10480	10790	11090	11400	11700	12000	12300	12600

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	120	6050	6240	6420	6600	6790	6970	7140	7320	7500
Dual	120	10810	11140	11470	11800	12120	12450	12770	13080	13400

TIRE DIMENSIONS

OVERALL DIAMETER	1060 mm
TIRE WIDTH	305 mm
STATIC LOADED RADIUS	493 mm
ROLLING CIRCUMFERENCE	3232 mm
MIN. DUAL SPACING	335 mm
PATTERN DEPTH	19.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	73 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/