

275/70R22.5 148/145M NOKIAN TYRES HAKKAPOLIITTA TRUCK E2

Superior traction and optimized performance on severe winter conditions

PRODUCT CODE	T675357
APPLICATION	Drive
LI / SPEED SYMBOL	148/145M
RIM RECOMMENDED	8.25
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0058474, E4 0414426 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	130	4860	5000	5150	5300	5440	5590	5730	5880	6020	6160	6300
Dual	130	8940	9220	9490	9760	10030	10290	10560	10820	11080	11340	11600

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	970 mm
TIRE WIDTH	275 mm
STATIC LOADED RADIUS	450 mm
ROLLING CIRCUMFERENCE	2922 mm
MIN. DUAL SPACING	311 mm
PATTERN DEPTH	17.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	74 dB
NOISE WAVES	B
STUDDABLE	Marked stud positions on tread Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/