

295/80R22.5 152/149M NOKIAN TYRES HAKKAPELIITTA TRUCK E2

Superior traction and optimized performance on severe winter conditions

| | |
|-------------------|--------------------------------|
| PRODUCT CODE | T675368 |
| APPLICATION | Drive |
| LI / SPEED SYMBOL | 152/149M |
| RIM RECOMMENDED | 9.00 |
| RIM PERMITTED | 9.75 |
| TYPE APPROVAL | E4 0061721, E4 0414426 S2W2R3B |



LOAD CAPACITY, KG

| Axle fitting | Speed (km/h) | Pressure (kPa) | | | | | | | | |
|--------------|--------------|----------------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | 650 | 675 | 700 | 725 | 750 | 775 | 800 | 825 | 850 |
| Single | 130 | 5730 | 5900 | 6080 | 6250 | 6420 | 6590 | 6760 | 6930 | 7100 |
| Dual | 130 | 10490 | 10810 | 11130 | 11450 | 11760 | 12070 | 12380 | 12690 | 13000 |

TIRE DIMENSIONS

| | |
|-----------------------|---------|
| OVERALL DIAMETER | 1055 mm |
| TIRE WIDTH | 302 mm |
| STATIC LOADED RADIUS | 492 mm |
| ROLLING CIRCUMFERENCE | 3184 mm |
| MIN. DUAL SPACING | 335 mm |
| PATTERN DEPTH | 19.5 mm |

EU-LABEL VALUES

| | |
|--------------------|---|
| ROLLING RESISTANCE | D |
| WET GRIP | C |
| NOISE | 73 dB |
| NOISE WAVES | A |
| STUDDABLE | Marked stud positions on tread Number of studs 168 pcs Recommended stud 11-15 |
| MARKINGS | M+S, SnowGrip, Traction, Regroovable |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/