

# 295/80R22.5 152/149M NOKIAN TYRES HAKKAPELIITTA TRUCK E2

Superior traction and optimized performance on severe winter conditions



PRODUCT CODE	T675368
APPLICATION	Drive
LI / SPEED SYMBOL	152/149M
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0061721, E4 0414426 S2W2R3B

## TIRE DIMENSIONS

STATIC LOADED RADIUS	19.4 in
ROLLING CIRCUMFERENCE	125.4 in
MIN. DUAL SPACING	13.2 in
PATTERN DEPTH	25/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	73 dB
NOISE WAVES	A
STUDDABLE	Marked stud positions on tread Number of studs 168 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)