

# 315/70R22.5 156/150L NOKIAN TYRES HAKKAPELIITTA TRUCK F2

Steering axle tire for demanding winter conditions

PRODUCT CODE	T675300
APPLICATION	Steer
LI / SPEED SYMBOL	156/150L (154/150M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058469, E4 0414425 S2W2R3B



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	120	6170	6360	6540	6730	6910	7100	7280	7460	7640	7820	8000
Dual	120	10330	10650	10960	11270	11580	11890	12200	12500	12800	13100	13400

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	130	6050	6240	6420	6600	6790	6970	7140	7320	7500
Dual	130	10810	11140	11470	11800	12120	12450	12770	13080	13400

## TIRE DIMENSIONS

OVERALL DIAMETER	1011 mm
TIRE WIDTH	311 mm
STATIC LOADED RADIUS	466 mm
ROLLING CIRCUMFERENCE	3093 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	14.5 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
STUDDABLE	Marked stud positions on tread Number of studs 144 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)