

315/70R22.5 156/150L NOKIAN TYRES HAKKAPELIITTA TRUCK F2

Steering axle tire for demanding winter conditions

PRODUCT CODE	T675300
APPLICATION	Steer
LI / SPEED SYMBOL	156/150L (154/150M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058469, E4 0414425 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	13605	14020	14420	14835	15235	15655	16050	16445	16845	17240	17635
Dual	75	22775	23480	24165	24845	25530	26215	26895	27560	28220	28880	29540

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	80	13340	13755	14155	14550	14970	15365	15740	16140	16535
Dual	80	23830	24560	25285	26015	26720	27450	28155	28835	29540

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	39.8 in
TIRE WIDTH	12.2 in
STATIC LOADED RADIUS	18.3 in
ROLLING CIRCUMFERENCE	121.8 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	18/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
STUDDABLE	Marked stud positions on tread Number of studs 144 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/