

# 265/70R19.5 143/141J NOKIAN TYRES HAKKAPOLIITTA TRUCK T

## Controlled trailer handling in winter conditions

PRODUCT CODE	T675358
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0054011, E4 0416953 S2W2R3B



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	62.5	9260	9545	9835	10095	10385	10670	10935	11200	11485	11750	12015
Dual	62.5	17505	18035	18565	19090	19620	20150	20655	21185	21695	22200	22710

## TIRE DIMENSIONS

OVERALL DIAMETER	34.3 in
TIRE WIDTH	10.2 in
STATIC LOADED RADIUS	15.9 in
ROLLING CIRCUMFERENCE	102.4 in
MIN. DUAL SPACING	11.6 in
PATTERN DEPTH	18/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	71 dB
NOISE WAVES	A
STUDDABLE	Marked stud positions on tread Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)