

315/80R22.5 156/150K NOKIAN TYRES R-TRUCK DRIVE

Sturdy drive axle tire for demanding on/off-road use

PRODUCT CODE	T675312
APPLICATION	Drive
LI / SPEED SYMBOL	156/150K
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058470, E4 0416949 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	67.5	14220	14660	15100	15520	15960	16380	16800	17220	17635
Dual	67.5	23830	24560	25285	26015	26720	27450	28155	28835	29540

TIRE DIMENSIONS

STATIC LOADED RADIUS	20 in
ROLLING CIRCUMFERENCE	129.2 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	27/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	75 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/