

315/80R22.5 156/150K NOKIAN TYRES R-TRUCK DRIVE

Sturdy drive axle tire for demanding on/off-road use

PRODUCT CODE	T675235
APPLICATION	Drive
LI / SPEED SYMBOL	156/150K
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0041150, E4 0210143 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)							
		650	675	700	725	750	775	800	825
Single	110	6610	6810	7010	7210	7410	7610	7810	8000
Dual	110	11070	11410	11750	12080	12420	12750	13070	13400

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	1076 mm
TIRE WIDTH	312 mm
STATIC LOADED RADIUS	500 mm
ROLLING CIRCUMFERENCE	3271 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	21 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	75 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/