

315/80R22.5 156/150K NOKIAN TYRES R-TRUCK STEER

For controlled steering both on and off-road

PRODUCT CODE	T675331
APPLICATION	Steer
LI / SPEED SYMBOL	156/150K
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058470, E4 0416950 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	110	6450	6650	6850	7040	7240	7430	7620	7810	8000
Dual	110	10810	11140	11470	11800	12120	12450	12770	13080	13400

TIRE DIMENSIONS

STATIC LOADED RADIUS	508 mm
ROLLING CIRCUMFERENCE	3282 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	16 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/