

## 385/65R22.5 164K NOKIAN TYRES R-TRUCK STEER

For controlled steering both on and off-road

PRODUCT CODE	T675313
APPLICATION	Steer
LI / SPEED SYMBOL	164K
RIM RECOMMENDED	11.75
RIM PERMITTED	12.25
TYPE APPROVAL	E4 0054010, E4 0416950 S2W2R3B



### LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	110	7710	7940	8180	8410	8640	8870	9100	9330	9550	9780	10000

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	1073 mm
TIRE WIDTH	386 mm
STATIC LOADED RADIUS	492 mm
ROLLING CIRCUMFERENCE	3248 mm
PATTERN DEPTH	16 mm

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)