

# 265/70R19.5 143/141J NOKIAN TYRES R-TRUCK TRAILER

## Reliability for on/off-road use

PRODUCT CODE	T675242
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0043501, E4 0210142 S2WR2



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	62.5	9700	9985	10295	10580	10870	11155	11440	11730	12015
Dual	62.5	18320	18895	19445	19995	20545	21100	21625	22180	22710

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	34.5 in
TIRE WIDTH	9.9 in
STATIC LOADED RADIUS	15.9 in
ROLLING CIRCUMFERENCE	105 in
MIN. DUAL SPACING	11.6 in
PATTERN DEPTH	19/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	E
WET GRIP	B
NOISE	73 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)